



PCIF BEARING LIMITED



35 mm x 72 mm x 17 mm skf 6207 bearing

Bearing No. 6207

6207 Bearing 2D drawings and 3D CAD models

| | |
|---|--------------------------|
| Size | 72x35x17 mm |
| Bore Diameter | 72 mm |
| Outer Diameter | 35 mm |
| Width | 17 mm |
| d | 35 mm |
| D | 72 mm |
| B | 17 mm |
| d ₁ | 46.94 mm |
| D ₂ | 62.69 mm |
| r _{1,2} - min. | 1.1 mm |
| d _a - min. | 42 mm |
| D _a - max. | 65 mm |
| r _a - max. | 1 mm |
| Basic dynamic load rating - C | 27 kN |
| Basic static load rating - C ₀ | 15.3 kN |
| Fatigue load limit - P _u | 0.655 kN |
| Reference speed | 20000 r/min |
| Limiting speed | 13000 r/min |
| Calculation factor - k _r | 0.025 |
| Calculation factor - f ₀ | 13.8 |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.293 |



PCIF BEARING LIMITED

| | |
|---------------------------------|--|
| EAN | 7316577067449 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 35MM Bore; 72MM Outside Diameter; 17MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | 6207 |
| Weight / LBS | 0.64 |
| Outside Diameter | 2.835 Inch 72 Millimeter |
| Outer Race Width | 0.669 Inch 17 Millimeter |
| Bore | 1.378 Inch 35 Millimeter |
| d ₁ | 46.94 mm |
| D ₂ | 62.69 mm |
| r _{1,2} min. | 1.1 mm |
| d _a min. | 42 mm |
| | |



PCIF BEARING LIMITED

| | |
|--------------------------------|----------|
| D_a max. | 65 mm |
| r_a max. | 1 mm |
| Basic dynamic load rating C | 27 kN |
| Basic static load rating C_0 | 15.3 kN |
| Fatigue load limit P_u | 0.655 kN |
| Calculation factor k_r | 0.025 |
| Calculation factor f_0 | 13.8 |
| Mass bearing | 0.29 kg |