



PCIF BEARING LIMITED



60 mm x 110 mm x 22 mm skf 6212 bearing

Bearing No. 6212

6212 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------------------|--------------------------|
| Size | 110x60x22 mm |
| Bore Diameter | 110 mm |
| Outer Diameter | 60 mm |
| Width | 22 mm |
| d | 60 mm |
| D | 110 mm |
| B | 22 mm |
| d ₁ | 75.5 mm |
| D ₂ | 98 mm |
| r _{1,2} - min. | 1.5 mm |
| d _a - min. | 69 mm |
| D _a - max. | 101 mm |
| r _a - max. | 1.5 mm |
| Basic dynamic load rating - C | 55.3 kN |
| Basic static load rating - C ₀ | 36 kN |
| Fatigue load limit - P _u | 1.5 kN |
| Reference speed | 13000 r/min |
| Limiting speed | 8000 r/min |
| Calculation factor - k _r | 0.025 |
| Calculation factor - f ₀ | 14.3 |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.789 |



PCIF BEARING LIMITED

| | |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EAN | 7316577085481 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 60MM Bore; 110MM Outside Diameter; 22MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | 6212 |
| Weight / LBS | 1.74 |
| Bore | 2.362 Inch 60 Millimeter |
| Outer Race Width | 0.866 Inch 22 Millimeter |
| Outside Diameter | 4.331 Inch 110 Millimeter |
| d ₁ | 75.5 mm |
| D ₂ | 98 mm |
| r _{1,2} min. | 1.5 mm |
| d _a min. | 69 mm |
| | |



PCIF BEARING LIMITED

| | |
|--------------------------------|---------|
| D_a max. | 101 mm |
| r_a max. | 1.5 mm |
| Basic dynamic load rating C | 55.3 kN |
| Basic static load rating C_0 | 36 kN |
| Fatigue load limit P_u | 1.53 kN |
| Calculation factor k_r | 0.025 |
| Calculation factor f_0 | 14.3 |
| Mass bearing | 0.78 kg |