




# PCIF BEARING LIMITED



110 mm x 170 mm x 28 mm skf 6022 bearing

Bearing No. 6022

6022 Bearing 2D drawings and 3D CAD models

Size	170x110x28 mm
Bore Diameter	170 mm
Outer Diameter	110 mm
Width	28 mm
d	110 mm
D	170 mm
B	28 mm
d <sub>1</sub>	129.05 mm
D <sub>2</sub>	155.3 mm
r <sub>1,2</sub> - min.	2 mm
d <sub>a</sub> - min.	119 mm
D <sub>a</sub> - max.	161 mm
r <sub>a</sub> - max.	2 mm
Basic dynamic load rating - C	85.2 kN
Basic static load rating - C <sub>0</sub>	73.5 kN
Fatigue load limit - P <sub>u</sub>	2.6 kN
Reference speed	8000 r/min
Limiting speed	5000 r/min
Calculation factor - k <sub>r</sub>	0.025
Calculation factor - f <sub>0</sub>	15.6
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.01



## PCIF BEARING LIMITED

EAN	7316576618208
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	110MM Bore; 170MM Outside Diameter; 28MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	6022
Weight / LBS	4.42
Outer Race Width	1.102 Inch   28 Millimeter
Outside Diameter	6.693 Inch   170 Millimeter
Bore	4.331 Inch   110 Millimeter
bore diameter:	110 mm
static load capacity:	73.5 kN
outside diameter:	170 mm
precision rating:	ABEC 1 (ISO Class



## PCIF BEARING LIMITED

	Normal)
overall width:	28 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	28 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	2 mm
snap ring included:	Without Snap Ring
maximum rpm:	5000 RPM
internal clearance:	C0
series:	60
dynamic load capacity:	85.2 kN
$d_1$	129.05 mm
$D_2$	155.3 mm
$r_{1,2}$ min.	2 mm
$d_a$ min.	119 mm
$D_a$ max.	161 mm
$r_a$ max.	2 mm
Basic dynamic load rating C	85.2 kN
Basic static load rating $C_0$	73.5 kN
Fatigue load limit $P_u$	2.6 kN
Calculation factor $k_r$	0.025
Calculation factor $f_0$	15.6
Mass bearing	1.97 kg