



# PCIF BEARING LIMITED



1211 ektn9 Bearing 2D drawings and 3D CAD models

55 mm x 100 mm x 21 mm skf 1211 ektn9 bearing

Bearing No. 1211 ektn9

Category	Self Aligning Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.71
EAN	7316576623509
Product Group	B00152
Mounting Method	Tapered Adapter
Enclosure	Open
Rolling Element	Ball Bearing
Adapter Sleeve	H-211
Cage Material	Polyamide
Precision Class	ABEC 1   ISO P0
Internal Clearance	C0-Medium
Number of Rows of Balls	Double Row
Other Features	Allowable Misalignment 2.5 Deg   High Capacity Design   1:12 Taper
Long Description	55MM Bore; Tapered Adapter Mount; 100MM Outside Diameter; 21MM Inner Race Width; 21MM Outer Race Width; Open; Polyamide Cage; Double Row of Balls; ABEC 1   ISO P0; C0-Medium
Inch - Metric	Metric
Category	Self Aligning Ball Bearings



## PCIF BEARING LIMITED

UNSPSC	31171532
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Self Aligning
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	1211 EKTN9
Weight / LBS	1.565
Inner Race Width	0.827 Inch   21 Millimeter
D	3.937 Inch   100 Millimeter
d	2.165 Inch   55 Millimeter
Outer Race Width	0.827 Inch   21 Millimeter
bore diameter:	55 mm
precision rating:	Not Rated
outside diameter:	100 mm
maximum rpm:	9000 RPM
overall width:	21 mm
cage material:	Fiberglass Reinforced Nylon
bore type:	Tapered 1:12
finish/coating:	Uncoated
closure type:	Open
maximum misalignment:	2.5 °
internal clearance:	C0
outer ring width:	21 mm
dynamic load capacity:	27.6 kN
fillet radius:	1.5 mm
static load capacity:	10.6 kN
series:	1200
d	55 mm
D	100 mm
B	21 mm
d <sub>1</sub>	70.3 mm
D <sub>1</sub>	86.5 mm



## PCIF BEARING LIMITED

$r_{1,2}$ min.	1.5 mm
$D_a$ max.	91 mm
$r_a$ max.	1.5 mm
Basic dynamic load rating C	27.6 kN
Basic static load rating $C_0$	10.6 kN
Fatigue load limit $P_u$	0.54 kN
Reference speed	14000 r/min
Limiting speed	9000 r/min
Permissible angular misalignment	2.5 °
Calculation factor $k_r$	0.04
Calculation factor e	0.19
Calculation factor $Y_0$	3.6
Calculation factor $Y_1$	3.3
Calculation factor $Y_2$	5.1
Mass bearing	0.71 kg