



PCIF BEARING LIMITED



75 mm x 95 mm x 10 mm skf 61815 bearing

Bearing No. 61815

61815 Bearing 2D drawings and 3D CAD models

Size	95x75x10 mm
Bore Diameter	95 mm
Outer Diameter	75 mm
Width	10 mm
d	75 mm
D	95 mm
B	10 mm
d ₁	81.7 mm
D ₁	88.7 mm
D ₂	90.7 mm
r _{1,2} - min.	1.3 mm
d _a - min.	78.2 mm
D _a - max.	91.8 mm
r _a - max.	0.6 mm
Basic dynamic load rating - C	12.5 kN
Basic static load rating - C ₀	10.8 kN
Fatigue load limit - P _u	0.585 kN
Reference speed	14000 r/min
Limiting speed	8500 r/min
Calculation factor - k _r	0.015
Calculation factor - f ₀	13.4
Category	Single Row Ball Bearings
Inventory	2.0
Manufacturer Name	SKF



PCIF BEARING LIMITED

Minimum Buy Quantity	N/A
Weight / Kilogram	0.166
EAN	7316577098290
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	75MM Bore; 95MM Outside Diameter; 10MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	61815 J
Weight / LBS	0.37
Outer Race Width	0.394 Inch 10 Millimeter
Outside Diameter	3.74 Inch 95 Millimeter
Bore	2.953 Inch 75 Millimeter
bore diameter:	75 mm
static load capacity:	14.3 kN



PCIF BEARING LIMITED

outside diameter:	95 mm
precision rating:	Not Rated
overall width:	10 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	10 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.6 mm
snap ring included:	Without Snap Ring
maximum rpm:	8500 RPM
internal clearance:	C0
series:	61
dynamic load capacity:	12.7 kN
d_1	81.7 mm
D_1	88.7 mm
D_2	90.7 mm
$r_{1,2}$ min.	1.3 mm
d_a min.	78.2 mm
D_a max.	91.8 mm
r_a max.	0.6 mm
Basic dynamic load rating C	12.5 kN
Basic static load rating C_0	10.8 kN
Fatigue load limit P_u	0.585 kN
Calculation factor k_r	0.015
Calculation factor f_0	13.4
Mass bearing	0.14 kg