




PCIF BEARING LIMITED



45 mm x 85 mm x 19 mm skf 7209 bep bearing

Bearing No. 7209 bep

7209 bep Bearing 2D drawings and 3D CAD models

Size	85x45x19 mm
Bore Diameter	85 mm
Outer Diameter	45 mm
Width	19 mm
d	45 mm
D	85 mm
B	19 mm
d ₁	60.85 mm
d ₂	52.68 mm
D ₁	70.15 mm
a	37 mm
r _{1,2} - min.	1.1 mm
r _{3,4} - min.	0.6 mm
d _a - min.	52 mm
D _a - max.	78 mm
D _b - max.	80.8 mm
r _a - max.	1 mm
r _b - max.	0.6 mm
Basic dynamic load rating - C	35.8 kN
Basic static load rating - C ₀	26 kN
Fatigue load limit - P _u	1.1 kN
Reference speed	9000 r/min
Limiting speed	9000 r/min
Calculation factor - k _r	0.095
Calculation factor - k _a	1.4



PCIF BEARING LIMITED

Calculation factor - e	1.14
Calculation factor - X	0.57
Calculation factor - Y ₀	0.52
Calculation factor - Y ₁	0.55
Calculation factor - Y ₂	0.93
Calculation factor - X	0.35
Calculation factor - Y ₀	0.26
Calculation factor - Y ₁	
Calculation factor - Y ₂	0.57
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.42
EAN	7316576633119
Product Group	B00308
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	45MM Bore; 85MM Outside Diameter; 19MM



PCIF BEARING LIMITED

	Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7209 BEP
Weight / LBS	0.917
Outside Diameter	3.346 Inch 85 Millimeter
Bore	1.772 Inch 45 Millimeter
Width	0.748 Inch 19 Millimeter
bore diameter:	45 mm
radial static load capacity:	26 kN
outside diameter:	85 mm
cage material:	Nylon
overall width:	19 mm
outer ring width:	19 mm
contact angle:	40 °
maximum rpm:	9000 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
fillet radius:	1 mm
radial dynamic load capacity:	35.8 kN
series:	72



PCIF BEARING LIMITED

d_1	60.85 mm
d_2	52.68 mm
D_1	70.15 mm
$r_{1,2}$ min.	1.1 mm
$r_{3,4}$ min.	0.6 mm
d_a min.	52 mm
D_a max.	78 mm
D_b max.	80.8 mm
r_a max.	1 mm
r_b max.	0.6 mm
Basic dynamic load rating C	35.8 kN
Basic static load rating C_0	26 kN
Fatigue load limit P_u	1.12 kN
Calculation factor A	0.012
Calculation factor k_r	0.095
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y_0	0.26
Calculation factor Y_2	0.57
Calculation factor X	0.57
Calculation factor Y_0	0.52
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Mass bearing	0.42 kg